

WHAT IS CLAIMED IS:

9/15/17

1. A siding boards attachment structure comprising:  
a starter fitting for supporting a siding board in the  
lowest portion;

5 a ground sill flashing disposed in a lower portion of said  
siding board in the lowest portion;

a furring strip for fixing said starter fitting; and  
said siding board supported by said starter fitting,  
wherein said starter fitting comprises:

10 a base plate portion having a planar rear side surface that  
is fixed to said furring strip;

a supporting portion for supporting siding boards bent  
forward from said base plate portion; and

15 spacing portions formed at left and right end portions of  
said base plate portion to have the cross sectional shape of a  
squarish letter U.

2. A siding boards attachment structure according to claim  
1, wherein

20 said starter fitting is disposed in a corner portion of a  
building,

in said starter fitting for the corner portion, said base  
plate portion comprises a first corner base plate and a second  
corner base plate which are substantially perpendicular to each  
25 other between said spacing portions formed at the left and right  
end portions of said base plate portion, and

said supporting portion is formed for each of said first

corner base plate and said second corner base plate.

3. A siding boards attachment structure according to claim 1, wherein each of said spacing portions has substantially the same thickness as at least a spaced distance between said siding board and said furring strip.

4. A siding boards attachment structure according to claim 1, wherein said supporting portion of said starter fitting comprises an engaging end portion formed by bending the end of said supporting portion slantly upward.

5. A siding boards attachment structure according to claim 1, wherein a bottom of each of said spacing portions extends lower than the position of said supporting portion.

6. A siding boards attachment structure according to claim 1, wherein said starter fitting and said ground sill flashing are individually fixed to said furring strip.

7. A siding boards attachment structure according to claim 6, wherein

said ground sill flashing comprises a step portion used for positional matching for a bottom of said starter fitting, and the bottom of said starter fitting abuts said step portion.

8. A siding boards attachment structure according to claim

1, wherein

said starter fitting is fixed to said furring strip,  
said ground sill flashing is fixed to a column at a position  
inwardly closer than the position of said furring strip.

5

9. A starter fitting for supporting siding boards in lowest  
portions of a building, comprising:

a base plate portion having a planar rear side surface that  
is configured to be fixed to a furring strip;

10

supporting portions for supporting siding boards bent  
forward from said base plate portion; and

spacing portions formed at left and right end portions of  
said base plate portion to have the cross sectional shape of a  
squarish letter U.

15

10. A starter fitting according to claim 9, wherein

said starter fitting is configured to be disposed in a  
corner portion of the building,

said starter fitting for the corner portion comprises a  
first corner base plate and a second corner base plate which are  
substantially perpendicular to each other between said spacing  
portions formed at the left and right end portions of said base  
plate portion, and

said supporting portion is formed for each of said first  
corner base plate and said second corner base plate.

25

11. A starter fitting according to claim 9, wherein each

91 of said supporting portion of said starter fitting comprises an engaging end portion formed by bending the end of said supporting portion slantly upward.

- 5 12. A starter fitting according to claim 9, wherein a bottom of each of said spacing portions extends lower than the position of said supporting portion.

09970671-100504

add  
a2